

Technical datasheet

PROMAX 30 SUPAFLUSH Cod.10.100.060		
PROMAX 30 SUPAFLUSH + Supameg Compact Cod. 10.100.061	PROMAX 30 SUPAFLUSH + trolley Cod. 10.100.062	PROMAX 30 SUPAFLUSH + trolley&Supameg Compact Cod. 10.100.063

DESCRIPTION

The Promax 30 New Supaflush pump is developed for flushing central heating systems to solve circulation and noise problems caused by accumulation of sludge, corrosion deposits and scale. The pump is able to operate easily at a pressure of 2 bar and efficiently clean up to 20 radiators. Working fluid temperature up to 50-55°C. The pump is fitted with:
Multifunction isolation/dump valves with protective plate and 90° rotating fresh water inlet tap;
Carrying bag with shoulder strap to contain hoses- funnel and selection of various fittings;
Optional trolley with large diameter “stair” wheels and handle that can be tilted up wards.

TECHNICAL FEATURES:

Tank:	27 lt
Dimensions (H*L*D):	58*45*30 cm
Max Flow Rate:	5400 l/h
Max Pressure:	2 bar
Power consumption:	0,45 HP
Weight (kg):	13
Protection:	IP54

ELEMENTS OF DISCALING PUMP

- 27 liters tank with large filling opening and underlying cap for easy and total cleaning;
- Double quick exhaust valves with external diameter 3/4";
- Protection cover;
- 90 ° faucet to restore water;
- Connecting pipes and filling funnel in a bag with handle and shoulder strap.

Optional

- Trolley (cod. 10.100.062 e cod. 10.100.063);
- Supameg Compact (cod. 10.100.061 e cod. 10.100.063).

