

SPC



- Domestic hot water production up to 65°C with R134a gas
- From -5° to 35°C external air temperature operation
- Programmable and remotable control panel
- Model with solar integration or integration with Luna Platinum+ (heating only models) (SPC-S)
- Electrical pulse titanium anode

		SPC 200 7213893	SPC 300 7112974	SPC 300 S 7112975
Product code		7213893	7112974	7112975
Capacity	l	217	271	265
Heat pump power	kW	1,7	1,7	1,7
Assorbed electrical power*	We	460	470	470
COP*		2,55	2,44	2,64
Integrated electrical resistance power	kW	1,8	1,8	1,8
Maximum working pressure	bar	10	10	10
Voltage supply	V	230	230	230
Air flow	m ³ /h	320	320	320
Min/max air temperature	°C	-5/+35	-5/+35	-5/+35
R134a coolant	kg	1,45	1,45	1,45
Mixed water at 40 °C V40**	l	289	385	380
Sound power level, indoor L _{WA} ***	dB(A)	57	57	57
Dimensions (h x Ø)	mm	1690 x 690	2000 x 690	2000 x 690
Empty weight	kg	92	105	123
Class				
Load profile		L	XL	XL

* Value for domestic water heating from 10°C to 54°C with air in entrance at 15°C

** Maximum DHW volume at 40°C

*** According to EN12102-2013